

RONCO

focus on quality

PRO-TEC™

5616

3-Ply Disposable Pleated Mask, ASTM F2100 Level-1



Available sizes

Item #	Color	Length ± 2 mm	Width ± 2 mm
5616	Blue	175	95

100 masks x 20 boxes = 2,000 masks per case

Features

- Excellent breathability and high comfort
- Good bacterial and particulate filtration efficiency
- Prevents respiratory droplets from spreading
- Adjustable nose clip, ear loops are ultrasonic-welded (no staples)
- Moderate resistance against bodily fluids and blood
- Fiberglass and latex free
- ASTM F2100-2019 level-1 rated

Applications

- Retail Pharmacies
- Beauty/Aesthetics
- Laboratory
- Medical
- Waste Management
- Clean Room Handling
- Dental Clinics
- Provides light filtration efficiency suitable for everyday use by the general public
- Reduces exposure to airborne particulates
- Moderately protects against the transfer of micro-organisms, body fluids and particulate matters

Storage & Handling

Store in original packaging in a cool, dry and well-ventilated area, away from dust, direct sunlight, moisture, X-ray and excessive heat above 37 °C (100 °F)



Performance



Particulate Filtration Efficiency (PFE) ≥ 95%
Bacterial Filtration Efficiency (BFE) ≥ 95%
Differential pressure < 5.0 mmH₂O/cm²
Synthetic Blood Penetration: Passed at 80 mmHg
Flammability: Class 1

Head Office

70 Planchet Road,
Concord, Ontario
L4K 2C7, Canada

1-905-660-6700
1-877-663-7735
contactus@roncosafety.com
www.roncosafety.com

Follow us @Roncosafety



Although reasonable care has been taken in the preparation of this document, no warranties are extended, and no liability is assumed. The information is solely provided as a general guideline for product use and care. It is up to end-users to determine the suitability of the products for their own intended purpose(s).